



CO2-R/A

CO2 air quality sensor for indoor with measuring range switching, analog output

Measuring size: CO2

Output: 0-10 V, 4-20 mA, Relay

Highlights: modern room housing, optional LDC-Display



Description

The indoor air quality sensor CO2-R/A registers the CO2 concentration in the air in the environment in a range from 0-10000 ppm via a nondispersive infrared sensor (NDIR) into a linear output signal 0-10 V respectively 4-20 mA.

As an option the air quality sensor has a potential-free changeover contact and a backlit display. The display content can be rotated in 90° steps using a menu and the measured value, the switching threshold set, the state of the relay, the MIN/MAX measured values for the selected intervals (1 h / 6 h / 12 h / 24 h) etc. can be read out.

3 different measuring ranges can be selected (0-2000 ppm, 0-5000 ppm, 0-10000 ppm) which can be switched, according to requirements, by the innovative DIP switching technology.

The zero point balance depending on the actual ambient conditions can be performed on the device by manual calibration. The quality sensor performs an automatic self-calibration at regular interval, thus ensuring a long-term stable CO2 measurement.



Technical Specifications

Measurement range CO ₂	0-10000 ppm, scales: 0-2000/5000/10000 ppm
Scales	0-2000/5000/10000 ppm
Accuracy	0-2000 ppm: ± 50 ppm + 2% f. mv, 0-5000 ppm: ± 50 ppm + 3% f. mv, else: ± 100 ppm + 5% f. mv (at 20°C, 1013 mbar, auto-calibration ON)
Temperature dependency	CO ₂ : ± 5 ppm / K
Pressure dependency	CO ₂ : 0,16% f. mv/hPa
Running-in time	10 min
Response time (t ₉₀)	< 5 min
Long term stability	$\pm 1\%$ FS/year
Sensor	Nondispersive infrared sensor (NDIR)
Sensor protection	mounted inside housing
Supply voltage	24 V AC/DC ($\pm 5\%$)
Current consumption	Ø 100 mA
Analogue output 0-10 V	3-wire connection
Analogue output 4-20 mA	3-wire connection
Alarm output	1 x potential-free change-over contact, 48 V, 1 A
Switching Hysteresis Relay	2% FS (without Display), 0,5...5% FS adjustable (with Display)
Electrical connection	screw terminals max. 1,5 mm ²
Housing	ABS polyman, colour signal white like RAL 9003
Cable gland	on the back or housing side (predetermined breaking point)
Display	optional LCD display with backlight on/off/auto
Dimensions	Housing: L 82 x W 82 x H 25 mm
Protection type	IP30, IP20 (with display)
Protection class	III
Working range r.H.	0...98% r.H. in contaminant-free, non-condensing air
Working temperature	0...+50°C
Storage temperature	-20...+50°C
Initial operation	After switch-on of the device follows a self-test and the tempering, which takes ca. 10 minutes depending on the environmental conditions. At this time the analogue output drifts from the actual measurement value.
Automatic calibration	<p>The automatic CO₂ calibration takes place every 7 days, this compensates for any drifts and achieves excellent long-term stability. To ensure this function, the device must be supplied with power for at least 7 days without interruption and ventilated once with fresh air (CO₂ 300...400 ppm) for approx. 10 minutes within this period. For the CO₂ calibration, the device saves the minimum CO₂ value measured during this period internally. After 7 days, this minimum value is normalized to 400 ppm CO₂ and the output signal corrected accordingly. The maximum correction is limited to half of the determined drift. If the measured value falls below approx. 300 ppm, the calibration is initialized to 400 ppm.</p> <p>The automatic calibration can be deactivated if necessary and performed manually.</p>
Manual calibration	<p>The manual CO₂ calibration of the output signal to 400 ppm (zero point) is started by pressing the button on the circuit board (hold it down for approx. 5 seconds until the LED flashes). Before that, continuous operation of min. 10 minutes in fresh air.</p> <p>The LED is deactivated after successful calibration.</p>



Installation	on-wall or on flush-mounted box
Approvals	CE, EAC, RoHS

Variants

Article Number		
CO2	Output CO2	Version CO2
CO2-R/A-I		
0-2000/5000/10000 ppm	4-20 mA	without Display
CO2-R/A-UI		
0-2000/5000/10000 ppm	0-10 V, 4-20 mA	without Display
CO2-R/A-UI6L		
0-2000/5000/10000 ppm	0-10 V, 4-20 mA	LED display
CO2-R/A-UID		
0-2000/5000/10000 ppm	0-10 V, 4-20 mA	with Display
CO2-R/A-UIR		
0-2000/5000/10000 ppm	0-10 V, 4-20 mA, Changer	without Display
CO2-R/A-UIR6L		
0-2000/5000/10000 ppm	0-10 V, 4-20 mA, Changer	LED display
CO2-R/A-UIRD		
0-2000/5000/10000 ppm	0-10 V, 4-20 mA, Changer	with Display

Accessories



FS9510
Table stand for room housing



motrona AX350
AX350: touchMATRIX® Process Indicator with two 16 bit Analog Inputs



motrona AX020
AX020: Process Indicator for Analog Signals



Dimensional Drawing

