



FS3060

Humidity transducer with contact block, active output (0-10 V or 4-20 mA)

Measuring size: rel. humidity

Output: 0-10 V, 4-20 mA, Relay

Highlights: heating function for condensation protection, easy-to-install surface-mounted housing



Description

The humidity transducer with contact block registers the relative humidity at the contact point contact prism/tube and converts this measured value into a line-ar output signal 0-10 V respectively 4-20 mA.

As an option the device has a potential-free changeover contact and a backlit display.

The display content can be rotated in 90° steps using a menu and the measured value, the switching threshold set, the state of the respective relay, the MIN/MAX measured values for the selected intervals (1 h / 6 h / 12 h / 24 h) etc. can be read out. The value measured in addition to the temperature can be selected from the 4 parameters % r.h., g/m³, g/kg, dp can easily be selected per DIP switch.

In addition the humidity measuring device has a heating function to protect the sensor at high humidity 95...99% r.h.. If the relative humidity exceeds the threshold value set ex-works for a certain period of time the heating function is activated. The sensor is heated for a limited time and thus dried and protected against condensation. During the heating and the subsequent temperature balancing phase the output signal is kept stable at the last measured value before the heating function was triggered.

The humidity sensor is very well protected against contamination by a sintered filter and can, if required, be finely calibrated in situ using an offset controller.



Technical Specifications

Measurement range r.H.	0-100% r.H.
Accuracy humidity	±3% r.H. (30-70% r.H., else ±5% r.H., at 20°C)
Temperature dependency	±0,02% r.H. / K (voltage output), ±0,04% r.H. / K (current version); ±0,05°C / 10 K (voltage version), ±0,07°C / 10 K (current output)
Long term stability	±1%/year
Sensor	capacitive humidity sensor
Sensor protection	sinter filter, sensor mounted inside the contact block
Flow rate	< 2 m/s
Supply voltage analog 0-10 V	24 V AC/DC (±5%)
Supply voltage analog 4-20 mA	15...36 V DC (U _{bmin} = 15 V + R _{Load} *0,02A)
Current consumption at 0-10 V	typ. 10 mA, 30 mA peak current consumption for 50 ms at switching moment at option relay
Current consumption at 4-20 mA	max. 20 mA / output, 40 mA peak current consumption for 50 ms at switching moment at option relay
Analogue output 0-10 V	3-wire connection, load current < 0,1 mA
Analogue output 4-20 mA	2-wire connection (transmitter), max. R _{Load} (Ohm) = (+U _b - 15 V) / 0,02 A
Alarm output	1 x potential-free change-over contact, 48 V, 1 A
Switching Hysteresis Relay	2% of the selected scaling (without display), 0,5...5% of the selected scaling adjustable (with display)
Electrical connection	screw terminals max. 1,5 mm ²
Housing	Polycarbonate PC UL 94 V0 with hinge locks, color signal white similar to RAL 9003
Cable gland	PG11 high-strength cable gland with strain relief
Display	optional LCD display with backlight (on/off/auto at 0-10 V version, at 4-20 mA version via DBL terminal)
Material	Contacting block: aluminium
Dimensions	Housing: L 89 x W 80 x H 47 mm, Contacting block: L 25 x W 54 x H 15 mm,
Protection type	Housing/electronic: IP65, Sensor: IP30
Protection class	III
Working range r.H.	0...98% r.H. in contaminant-free, non-condensing air
Working temperature	Probe: -20...+80°C, Electronic: 0...+50°C
Storage temperature	0...+50°C
Installation	clamping band, band width 9 mm, chucking capacity 50-110 mm, galvanized steel (in scope of delivery)
Approvals	CE, RoHS



Variants

Article Number		
Humidity	Output r.H.	Equipment
FS3060-I-H1-D		
0-100% r.H.	4-20 mA	LCD-Display
FS3060-I-H1-DR		
0-100% r.H.	4-20 mA	LCD-Display, Relay
FS3060-I-H1-R		
0-100% r.H.	4-20 mA	Relay
FS3060-I-H1-X		
0-100% r.H.	4-20 mA	-
FS3060-U-H1-D		
0-100% r.H.	0-10 V	LCD-Display
FS3060-U-H1-DR		
0-100% r.H.	0-10 V, changer	LCD-Display, Relay
FS3060-U-H1-R		
0-100% r.H.	0-10 V, changer	Relay
FS3060-U-H1-X		
0-100% r.H.	0-10 V	-

Accessories

SZ/E

Accessories



motrona AX350

AX350: touchMATRIX® Process Indicator with two 16 bit Analog Inputs



motrona AX020

AX020: Process Indicator for Analog Signals





Dimensional Drawing

