



MJP/E

Sheathed thermocouple type J with 2 m PVC-cable

Measuring size: temperature

Output: Type J

Highlights: bendable, mantle material: stainless steel



Description

A temperature measurement by sheath thermocouple is suitable for detection of high temperatures. The thermocouples can be used in gaseous as well as in liquid media. By treatment into fire-resistant magnesium oxide they are resistant to an adverse environmental conditions (pressure, vibration, abrasion) and therefore can guarantee a long lifetime. Due to a high mechanical capacity a sheath thermocouple are used predominantly in the industry and in the plant engineering.

Technical Specifications

Measurement range temp.	-220...+850°C
Thermocouple	Fe-CuNi, type J according to DIN EN 60584, IEC 584 (potential free)
Accuracy	class 1 ($\pm 1,5$ K up to 375°C, else $0,004 * t $)
Response time (t90)	< 1 s (class 1)
Isolation	magnesiumoxid (MgO, high compressed)
Cable	2 m PVC cable (max. +105°C) with core cable ends
Leakage resistance	> 50MΩ, at +20°C (250V DC)
Thermocouple size	Ø 1,0 - 6,0 mm, 150 - 500 mm (other on request)
Mantle material	stainless steel 1.4541
Dimensions	Change-over sleeve: 5 x 36 mm (standard), 7 x 36 mm by sleeve diameter Ø6 mm
Protection type	IP65
Installation	immersion sleeve, mounting flange, compression fitting (not in scope of delivery)
Approvals	CE, EAC, RoHS



Variants


Article Number		
Thermocouple	Sleeve diameter	Sleeve length
MJP/E-1.0/150-2		
type J	1,0 mm	150 mm
MJP/E-1.0/250-2		
type J	1,0 mm	250 mm
MJP/E-1.0/350-2		
type J	1,0 mm	350 mm
MJP/E-1.0/500-2		
type J	1,0 mm	500 mm
MJP/E-1.5/150-2		
type J	1,5 mm	150 mm
MJP/E-1.5/250-2		
type J	1,5 mm	250 mm
MJP/E-1.5/350-2		
type J	1,5 mm	350 mm
MJP/E-1.5/500-2		
type J	1,5 mm	500 mm
MJP/E-3.0/150-2		
type J	3,0 mm	150 mm
MJP/E-3.0/250-2		
type J	3,0 mm	250 mm
MJP/E-3.0/350-2		
type J	3,0 mm	350 mm
MJP/E-3.0/500-2		
type J	3,0 mm	500 mm
MJP/E-6.0/150-2		
type J	6,0 mm	150 mm
MJP/E-6.0/250-2		
type J	6,0 mm	250 mm
MJP/E-6.0/350-2		
type J	6,0 mm	350 mm
MJP/E-6.0/500-2		
type J	6,0 mm	500 mm



Accessories



KV/E
Compression Clamp



ST/E
Connector



Dimensional Drawing

