



RF5/R

Room Temperature Sensor with Poti, Push-Button and 2 LEDs

Measuring size: temperature

Output: passive sensor

Highlights: with potentiometer, push-button and 2 LEDs



Description

Room temperature sensor of the series RF5/R is the ideal and cost-efficient solution for inner room uses in the HVAC applications. The simple functional housing enables a simple installation. The temperature signal is available as passive output. The lower parts will be screwed directly at the wall with a help of 2 fixing screw (not in scope of delivery) or of an adapter frames. By the installation pay attention that the ventilation slit stands vertically to the wall. An exact temperature measurement can be guaranteed by the good air circulation.

Technical Specifications

Measurement range temp.	-30...+60°C
Sensor	Pt100, Pt500, Pt1000, Ni1000, KTY, NTC, LM235Z (other on request)
Circuit type	2-wire connection
Measurement current	approx. 1 mA
Electrical connection	screw terminals max. 1,5 mm ²
Leakage resistance	> 100 MOhm, at +20°C (500 V DC)
Housing	ABS polyman, colour signal white like RAL 9003
Cable gland	on the back or housing side (predetermined breaking point)
Equipment	1 kOhm Poti (±5%), 1 push-button (white), 1 LED (24 V DC, green), 1 LED (24 V DC, red)
Dimensions	Housing: L 82 x W 82 x H 25 mm
Protection type	IP30
Protection class	III
Storage temperature	-20...+70°C
Installation	on-wall or on flush-mounted box
Approvals	CE, EAC, RoHS
Notice	On-wall temperature probes are customized products and non-returnable.



Variants

Article Number	
Sensor	Equipment
RF5/R-10	
Pt100 (DIN EN 60751 Cl. B)	1 kOhm Poti ($\pm 5\%$), 1 button (white), 2 LED (24 V DC, green+red)
RF5/R-20	
Pt1000 (DIN EN 60751 Kl. B)	1 kOhm Poti ($\pm 5\%$), 1 button (white), 2 LED (24 V DC, green+red)
RF5/R-30	
Ni1000 (whirl-sintered)	1 kOhm Poti ($\pm 5\%$), 1 button (white), 2 LED (24 V DC, green+red)
RF5/R-40	
Ni1000TK5000 (whirl-sintered)	1 kOhm Poti ($\pm 5\%$), 1 button (white), 2 LED (24 V DC, green+red)
RF5/R-50	
NTC1,8k ($\pm 1\%$)	1 kOhm Poti ($\pm 5\%$), 1 button (white), 2 LED (24 V DC, green+red)
RF5/R-60	
LM235Z ($\pm 1\%$)	1 kOhm Poti ($\pm 5\%$), 1 button (white), 2 LED (24 V DC, green+red)
RF5/R-70	
NTC20k ($\pm 1\%$)	1 kOhm Poti ($\pm 5\%$), 1 button (white), 2 LED (24 V DC, green+red)
RF5/R-80	
NTC10k ($\pm 1\%$)	1 kOhm Poti ($\pm 5\%$), 1 button (white), 2 LED (24 V DC, green+red)



Accessories



FS9510

Table stand for room housing



Dimensional Drawing

